



TABLE OF CONTENTS

1. INTRODUCTION

| | | |
|-----|---|-----|
| 1.1 | Definition of an Ordinary Standard Bridge | 1-1 |
| 1.2 | Types of Components Addressed in the SDC | 1-2 |
| 1.3 | Bridge Systems | 1-2 |
| 1.4 | Local and Global Behavior | 1-3 |

2. DEMANDS ON STRUCTURE COMPONENTS

| | | |
|---------|---|-----|
| 2.1 | Ground Motion Representation | 2-1 |
| 2.1.1 | Spectral Acceleration | 2-1 |
| 2.1.2 | Horizontal Ground Motion | 2-1 |
| 2.1.3 | Vertical Ground Motion | 2-2 |
| 2.1.4 | Vertical/Horizontal Load Combination | 2-2 |
| 2.1.5 | Damping | 2-2 |
| 2.2 | Displacement Demand | 2-3 |
| 2.2.1 | Estimated Displacement | 2-3 |
| 2.2.2 | Global Structure Displacement and Local Member Displacement | 2-4 |
| 2.2.3 | Displacement Ductility Demand | 2-4 |
| 2.2.4 | Target Displacement Ductility Demand | 2-4 |
| 2.3 | Force Demand | 2-8 |
| 2.3.1 | Moment Demand | 2-8 |
| 2.3.2 | Shear Demand | 2-8 |
| 2.3.2.1 | Column Shear Demand | 2-8 |
| 2.3.2.2 | Pier Wall Shear Demand | 2-8 |
| 2.3.3 | Shear Demand for Capacity Protected Members | 2-8 |



TABLE OF CONTENTS

3. CAPACITIES OF STRUCTURE COMPONENTS

| | | |
|---------|--|------|
| 3.1 | Displacement Capacity of Ductile Concrete Members | 3-1 |
| 3.1.1 | Ductile Member Definition | 3-1 |
| 3.1.2 | Distinction Between Local Member Capacity & Global Structure System Capacity | 3-1 |
| 3.1.3 | Local Member Displacement Capacity | 3-1 |
| 3.1.4 | Local Member Displacement Ductility Capacity | 3-3 |
| 3.1.4.1 | Minimum Local Displacement Ductility Capacity | 3-3 |
| 3.2 | Material Properties for Concrete Components | 3-5 |
| 3.2.1 | Expected Material Properties | 3-5 |
| 3.2.2 | Nonlinear Reinforcing Steel Models for Ductile Reinforced Concrete Members | 3-5 |
| 3.2.3 | Reinforcing Steel A706/A706M (Grade 60/Grade 400) | 3-5 |
| 3.2.4 | Nonlinear Prestressing Steel Model | 3-6 |
| 3.2.5 | Nonlinear Concrete Models for Ductile Reinforced Concrete Members | 3-8 |
| 3.2.6 | Normal Weight Portland Cement Concrete Properties | 3-8 |
| 3.2.7 | Other Material Properties | 3-9 |
| 3.3 | Plastic Moment Capacity for Ductile Concrete Members | 3-9 |
| 3.3.1 | Moment Curvature ($M-\phi$) Analysis | 3-9 |
| 3.4 | Requirements for Capacity Protected Components | 3-10 |
| 3.5 | Minimum Lateral Strength | 3-10 |
| 3.6 | Seismic Shear Design for Ductile Concrete Members | 3-11 |
| 3.6.1 | Nominal Shear Capacity | 3-11 |
| 3.6.2 | Concrete Shear Capacity | 3-11 |
| 3.6.3 | Shear Reinforcement Capacity | 3-12 |
| 3.6.4 | <i>Deleted</i> | 3-12 |
| 3.6.5 | Maximum and Minimum Shear Reinforcement Requirements for Columns | 3-13 |
| 3.6.5.1 | Maximum Shear Reinforcement | 3-13 |
| 3.6.5.2 | Minimum Shear Reinforcement | 3-13 |
| 3.6.5.3 | Minimum Vertical Reinforcement in Interlocking Portion | 3-13 |
| 3.6.6 | Shear Capacity of Pier Walls | 3-13 |
| 3.6.6.1 | Shear Capacity in the Weak Direction | 3-13 |
| 3.6.6.2 | Shear Capacity in the Strong Direction | 3-13 |
| 3.6.7 | Shear Capacity of Capacity Protected Members | 3-14 |
| 3.7 | Maximum and Minimum Longitudinal Reinforcement | 3-14 |
| 3.7.1 | Maximum Longitudinal Reinforcement | 3-14 |

| | | |
|-------|---|------|
| 3.7.2 | Minimum Longitudinal Reinforcement | 3-14 |
| 3.7.3 | Maximum Reinforcement Ratio | 3-14 |
| 3.8 | Lateral Reinforcement of Ductile Members | 3-14 |
| 3.8.1 | Lateral Reinforcement Inside the Analytical Plastic Hinge Length | 3-14 |
| 3.8.2 | Lateral Column Reinforcement Inside the Plastic Hinge Region | 3-15 |
| 3.8.3 | Lateral Column Reinforcement Outside the Plastic Hinge Region | 3-15 |
| 3.8.4 | Lateral Reinforcement of Pier Walls | 3-15 |
| 3.8.5 | Lateral Reinforcement Requirements for Columns Supported on Type II Pile Shafts | 3-15 |
| 3.8.6 | Lateral Confinement for Type II Pile Shafts | 3-15 |

4. DEMAND VS. CAPACITY

| | | |
|---------|---|-----|
| 4.1 | Performance Criteria | 4-1 |
| 4.1.1 | Global Displacement Criteria | 4-1 |
| 4.1.2 | Demand Ductility Criteria | 4-1 |
| 4.1.3 | Capacity Ductility Criteria | 4-1 |
| 4.2 | P-Δ Effects | 4-3 |
| 4.3 | Component Overstrength Factors | 4-3 |
| 4.3.1 | Column Overstrength Factor | 4-3 |
| 4.3.2 | Superstructure/Bent Cap Demand & Capacity | 4-4 |
| 4.3.2.1 | Longitudinal Superstructure Capacity | 4-5 |
| 4.3.2.2 | Bent Cap Capacity | 4-5 |
| 4.3.3 | Foundation Capacity | 4-6 |

5. ANALYSIS

| | | |
|-------|---|-----|
| 5.1 | Analysis Requirements | 5-1 |
| 5.1.1 | Analysis Objective | 5-1 |
| 5.2 | Analytical Methods | 5-1 |
| 5.2.1 | Equivalent Static Analysis (ESA) | 5-1 |
| 5.2.2 | Elastic Dynamic Analysis (EDA) | 5-1 |
| 5.2.3 | Inelastic Static Analysis (ISA) | 5-2 |
| 5.3 | Structural System “Global” Analysis | 5-2 |



TABLE OF CONTENTS

| | | |
|---------|---|-----|
| 5.4 | Stand-Alone “Local” Analysis | 5-3 |
| 5.4.1 | Transverse Stand-Alone Analysis | 5-3 |
| 5.4.2 | Longitudinal Stand-Alone Analysis | 5-4 |
| 5.5 | Simplified Analysis | 5-4 |
| 5.6 | Effective Section Properties | 5-5 |
| 5.6.1 | Effective Section Properties for Seismic Analysis | 5-5 |
| 5.6.1.1 | I_{eff} for Ductile Members | 5-5 |
| 5.6.1.2 | I_{eff} for Box Girder Superstructures | 5-5 |
| 5.6.1.3 | I_{eff} for Other Superstructure Types | 5-5 |
| 5.6.2 | Effective Torsional Moment of Inertia | 5-7 |
| 5.7 | Effective Member Properties for Non-Seismic Loading | 5-7 |

6. SEISMICITY AND FOUNDATION PERFORMANCE

| | | |
|----------|--------------------------------------|-----|
| 6.1 | Site Assessment | 6-1 |
| 6.1.1 | Seismicity and Foundation Data | 6-1 |
| 6.1.2 | ARS Curves | 6-1 |
| 6.1.2.1 | Standard ARS Curves | 6-1 |
| 6.1.2.2 | Site Specific ARS Curves | 6-2 |
| 6.2 | Foundation Design | 6-2 |
| 6.2.1 | Foundation Performance | 6-2 |
| 6.2.2 | Soil Classification | 6-2 |
| 6.2.2(A) | Competent Soil | 6-3 |
| 6.2.2(B) | Poor Soil | 6-3 |
| 6.2.2(C) | Marginal Soil | 6-3 |
| 6.2.3 | Foundation Design Criteria | 6-4 |
| 6.2.3.1 | Foundation Strength | 6-4 |
| 6.2.3.2 | Foundation Flexibility | 6-4 |

7. DESIGN

| | | |
|---------|---|------|
| 7.1 | Frame Design | 7-1 |
| 7.1.1 | Balanced Stiffness | 7-1 |
| 7.1.2 | Balanced Frame Geometry | 7-2 |
| 7.1.3 | Adjusting Dynamic Characteristics | 7-2 |
| 7.1.4 | End Span Considerations | 7-2 |
| 7.2 | Superstructure | 7-4 |
| 7.2.1 | Girders | 7-4 |
| 7.2.1.1 | Effective Superstructure Width | 7-4 |
| 7.2.2 | Vertical Acceleration | 7-4 |
| 7.2.3 | Pre-cast Girders | 7-6 |
| 7.2.4 | Slab Bridges | 7-6 |
| 7.2.5 | Hinges | 7-6 |
| 7.2.5.1 | Longitudinal Hinge Performance | 7-6 |
| 7.2.5.2 | Transverse Hinge Performance | 7-6 |
| 7.2.5.3 | Frames Meeting the Requirements of Section 7.1.2 | 7-6 |
| 7.2.5.4 | Hinge Seat Width for Frames Meeting the Requirements of Section 7.1.2 | 7-7 |
| 7.2.5.5 | Frames Not Meeting the Requirements of Section 7.1.2 | 7-8 |
| 7.2.6 | Hinge Restrainers | 7-8 |
| 7.2.7 | Pipe Seat Extenders | 7-9 |
| 7.2.8 | Equalizing Bolts | 7-9 |
| 7.3 | Bent Caps | 7-9 |
| 7.3.1 | Integral Bent Caps | 7-9 |
| 7.3.1.1 | Effective Bent Cap Width | 7-9 |
| 7.3.2 | Non-Integral Bent Caps | 7-10 |
| 7.3.2.1 | Minimum Bent Cap Seat Width | 7-10 |
| 7.3.3 | <i>Deleted</i> | 7-10 |
| 7.3.4 | Bent Cap Depth | 7-10 |
| 7.4 | Superstructure Joint Design | 7-10 |
| 7.4.1 | Joint Performance | 7-10 |
| 7.4.2 | Joint Proportioning | 7-10 |
| 7.4.2.1 | Minimum Bent Cap Width | 7-11 |
| 7.4.3 | Joint Description | 7-11 |
| 7.4.4 | T Joint Shear Design | 7-11 |



TABLE OF CONTENTS

| | | |
|-----------|---|------|
| 7.4.4.1 | Principal Stress Definition | 7-11 |
| 7.4.4.2 | Minimum Joint Shear Reinforcement | 7-12 |
| 7.4.4.3 | Joint Shear Reinforcement | 7-13 |
| 7.4.5 | Knee Joints | 7-14 |
| 7.5 | Bearings | 7-18 |
| 7.5.1 | Elastomeric Bearings | 7-18 |
| 7.5.2 | Sliding Bearings | 7-18 |
| 7.6 | Columns & Pier Walls | 7-18 |
| 7.6.1 | Column Dimensions | 7-18 |
| 7.6.2 | Analytical Plastic Hinge Length | 7-18 |
| 7.6.3 | Plastic Hinge Region | 7-19 |
| 7.6.4 | Multi-Column Bents | 7-19 |
| 7.6.5 | Column Flares | 7-19 |
| 7.6.5.1 | Horizontally Isolated Column Flares | 7-19 |
| 7.6.5.2 | Lightly Reinforced Column Flares | 7-20 |
| 7.6.5.3 | Flare Reinforcement | 7-20 |
| 7.6.6 | Pier Walls | 7-20 |
| 7.6.7 | Column Key Design | 7-20 |
| 7.7 | Foundations | 7-21 |
| 7.7.1 | Footing Design | 7-21 |
| 7.7.1.1 | Pile Foundations in Competent Soil | 7-21 |
| 7.7.1.2 | Pile Foundations in Marginal Soil | 7-23 |
| 7.7.1.2.1 | Lateral Design | 7-23 |
| 7.7.1.2.2 | Lateral Capacity of Fixed Head Piles | 7-24 |
| 7.7.1.2.3 | Passive Earth Resistance for Pile Caps in Marginal Soil | 7-24 |
| 7.7.1.3 | Rigid Footing Response | 7-24 |
| 7.7.1.4 | Footing Joint Shear | 7-24 |
| 7.7.1.5 | Effective Footing Width for Flexure | 7-26 |
| 7.7.1.6 | Effects of Large Capacity Piles on Footing Design | 7-26 |
| 7.7.1.7 | Use of "T" Headed Stirrups and Bars in Footings | 7-26 |
| 7.7.2 | Pier Wall Pile Foundations | 7-26 |
| 7.7.2.1 | Pier Wall Spread Footing Foundations | 7-27 |
| 7.7.3 | Pile Shafts | 7-27 |
| 7.7.3.1 | Shear Demand on Type I Pile Shafts | 7-27 |



| | | |
|---------|--|------|
| 7.7.3.2 | Flexure Demand/Capacity Requirements for Type II Pile Shafts | 7-27 |
| 7.7.3.3 | Pile Shaft Diameter | 7-27 |
| 7.7.3.4 | Minimum Pile Shaft Length | 7-28 |
| 7.7.3.5 | Enlarged Pile Shafts | 7-28 |
| 7.7.4 | Pile Extensions | 7-28 |
| 7.8 | Abutments | 7-28 |
| 7.8.1 | Longitudinal Abutment Response | 7-28 |
| 7.8.2 | Transverse Abutment Response | 7-31 |
| 7.8.3 | Abutment Seat Width | 7-31 |
| 7.8.4 | Abutment Shear Key Design | 7-32 |

8. SEISMIC DETAILING

| | | |
|---------|---|-----|
| 8.1 | Splices in Reinforcing Steel | 8-1 |
| 8.1.1 | No Splice Regions in Ductile Components | 8-1 |
| 8.1.2 | Reinforcement Spliced in Ductile Components & Components Expected to Accept Damage | 8-1 |
| 8.1.3 | Reinforcement Spliced in Capacity Protected Members | 8-1 |
| 8.1.4 | Hoop and Spiral Reinforcement Splices | 8-1 |
| 8.2 | Development of Longitudinal Column Reinforcement | 8-1 |
| 8.2.1 | Minimum Development Length of Reinforcing Steel for Seismic Loads | 8-2 |
| 8.2.2 | Anchorage of Bundled Bars in Ductile Components | 8-2 |
| 8.2.3 | Flexural Bond Requirements for Columns | 8-2 |
| 8.2.3.1 | Maximum Bar Diameter | 8-2 |
| 8.2.4 | Development Length for Column Reinforcement Extended Into Enlarged Type II Shafts | 8-3 |
| 8.2.5 | Maximum Spacing for Lateral Reinforcement | 8-3 |

APPENDICES

| | | |
|------------|----------------------------|--------|
| Appendix A | Notations & Acronyms | A1-A7 |
| Appendix B | ARS Curves | B1-B14 |
| Appendix C | Bibliography | C1 |



TABLE OF CONTENTS

FIGURES

| | | |
|--------------------|---|---------|
| Figure 2.1 | Local-Global Axis Definition | 2-2 |
| Figure 2.2 | The Effects of Foundation Flexibility on Force-Deflection Curve of a Single Column Bent | 2-5 |
| Figure 2.3 | The Effects of Bent Cap and Foundation Flexibility on Force-Deflection Curve of a Bent Frame | 2-6 |
| Figure 2.4 | Pile Shaft Definitions | 2-7 |
| Figure 3.1 | Local Displacement Capacity – Cantilever Column w/Fixed Base | 3-2 |
| Figure 3.2 | Local Displacement Capacity – Framed Column, Assumed as Fixed-Fixed | 3-3 |
| Figure 3.3 | Local Ductility Assessment | 3-4 |
| Figure 3.4 | Steel Stress Strain Model | 3-6 |
| Figure 3.5 | Prestressing Strand Stress Strain Model | 3-7 |
| Figure 3.6 | Concrete Stress Strain Model | 3-9 |
| Figure 3.7 | Moment Curvature Curve | 3-10 |
| Figure 3.8 | Concrete Shear Factors | 3-12 |
| Figure 4.1 | Global Force Deflection Relationship | 4-2 |
| Figure 4.2 | P-D Effects on Bridge Columns | 4-3 |
| Figure 4.3 | Superstructure Demand Generated by Column Overstrength Moment | 4-5 |
| Figure 4.4 | Capacity Provided by Superstructure Internal Resultant Force Couple | 4-5 |
| Figure 5.1 | EDA Modeling Techniques | 5-3 |
| Figure 5.2 | Stand-Alone Analysis | 5-4 |
| Figure 5.3 | Effective Stiffness of Cracked Reinforced Concrete Sections | 5-6 |
| Figure 7.1 | Balanced Stiffness | 7-3 |
| Figure 7.2 | Effective Superstructure Width | 7-5 |
| Figure 7.3 | Equivalent Static Vertical Loads & Moments | 7-5 |
| Figure 7.4 | Seat Width Requirements | 7-7 |
| Figure 7.5 | Effective Bent Cap Width | 7-9 |
| Figure 7.6 | Joint Shear Stresses in T Joints | 7-12 |
| Figure 7.7 | Location of Vertical Joint Reinforcement | 7-14 |
| Figure 7.8 | Joint Shear Reinforcement Details | 7-15 |
| Figure 7.9 | Location of Horizontal Joint Shear Steel | 7-16 |
| Figure 7.10 | Additional Joint Shear Steel for Skewed Bridges | 7-17 |
| Figure 7.11 | Footing Force Equilibrium | 7-21 |
| Figure 7.12 | Simplified Pile Model for Foundations in Competent Soil | 7-23 |
| Figure 7.13 | Assumed Effective Dimensions for Footing Joint Stress Calculation | 7-25 |
| Figure 7.14A/ B/ C | Effective Abutment Stiffness/ Area/ Width for Skewed Bridges | 7-29/30 |
| Figure 7.15 | Abutment Seat Width Requirements | 7-32 |